

Oasis Block Filler

Description:	Oasis Block Filler is emulsion putty, based on special acrylic copolymer resin. It is designed for filling and levelling the porosity and surface imperfections. Unlike other putties, it can be applied at higher thickness up to 10 mm. It is tough and non sandable and provides a levelled surface with excellent adhesion and low shrinkage. Also helps additional economy by reducing consumption of the topcoat paint on porous surfaces.
Recommended Usage:	Recommended as exterior putty for concrete, plaster, gypsum, masonry works. It is used to fill blow holes in the concrete precast as also for filling up open grains of hard wood, MDF and other wooden surfaces to obtain a smooth and even surface.
Pack Size:	1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Matt
Colour range:	Off white & Grey
Volume (Solids. %):	55 ± 2%
Specific gravity:	1.71± 0.05
Theoretical spread rate:	Depends on the surface cavities and imperfection
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will depend according to temperature, humidity and film thickness and will be vary accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1-2 hours
Recoat window:	Minimum 12 hours
Recommended System:	<ul style="list-style-type: none"> • On new and bare surfaces prime with 1 coat Oasis Acrylic Primer (W.B) • 2 coats Oasis Block filler. • Oasis recommended system <p>For best colour consistency use sufficient tinted / colored paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>
Surface Preparation:	<ul style="list-style-type: none"> • Surfaces must be sound, clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose or flaking material must be removed by scraping or brushing with a stiff bristle brush.
Application:	<ul style="list-style-type: none"> • Stir thoroughly before use • Use scraper, Knife, Blade. • Ready to use* [Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts paint.] • Avoid painting in direct sunlight • Store the paint in a cool place.



Oasis Block Filler

Advantages:

Versatile body filler, hides and levels surface imperfections and porosity, facilitates maximum performance of topcoat, comparatively less volume shrinkage, easy to apply, excellent adhesion.

Health, Safety and

Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes.
- Do not empty into drains.
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

