

TECHNICAL DATA



PRODUCT : OASIS HI-BUILD (SOFT)

Description	: A high quality acrylic co-polymer resin based heavy textured coating giving a soft rippled texture. Ideally suited for use on ceilings or as a general interior/exterior coating.
Volume Solids (%)	: 60 ± 2
Flash Point	: Not Applicable.
Specific Gravity (kg/ltr)	: 1.62 ± 0.02
Colours	: As per colour card.
Pack Size	: 5 US Gallon.
Theoretical Spread Rate (m ² /ltr)	: 2 to 3 <i>Spreading rates are calculated and due allowance for loss and wastage should be made.</i>
Drying Time to Touch	: 2 hours.
Drying Time to Overcoat	: 10 to 12 hours.
Cleanser or Thinner	: Water.
Application Notes	: Use either a smooth or textured foam roller, depending on finish required. Spread evenly on the surface, then "lay off" the texture with one light pass of the roller from top to bottom.
Application Methods	: Roller. (Depending on texture required cotton or sponge roller may be used)
Surface Preparation	: Ensure surface is dry and free of oil, grease, dust, efflorescence, loose particles, powder paint, etc.

SYSTEM INFORMATION

Newly Plastered or Rendered Interiors/Exteriors

1 coat Oasis Fine Primer/Oasis Acrylic Primer
1 coat Oasis Hi-Build (Soft)

Previously Painted Surfaces

1 coat Oasis Hi-Build (Soft)

Timber

1 coat Oasis Wood Primer
1 coat Oasis Hi-Build (Soft)

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION

(READ THIS SECTION BEFORE USE)

WATER BASED PAINT PRODUCT

- Ensure good ventilation during application and drying. Do not breathe vapour/spray.
- When applying by spray indoors, the wearing of air supplied breathing equipment will always be necessary. All respiratory equipment must be suitable for the purpose and meet an appropriate standard.
- When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Remove splashes from skin, use soap and water or a recognised skin cleaner.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty contents into wadis, drains or watercourses.
- Contains no added mercury.

*This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department

AL GURG LEIGH'S PAINTS L.L.C.

P.O. Box 22334, Sharjah, U.A.E. Tel.: (+971) 6 5343919, Fax: (+971) 6 5343983
P.O. Box 70024, Abu Dhabi, U.A.E. Tel.: (+971) 2 6723329, Fax: (+971) 2 6726671
E-mail: Enquiries@algurleighpaint.ae



Cert. Regn. No.: 0410021840