



# OASIS HIGH BUILD TRAFFIC PAINT (C.R)

## PRODUCT HEALTH AND SAFETY DATA

**Product Reference** : Oasis High Build Traffic Paint (C.R.)  
**Date of Issue** : 20/06/2010

**Issue** : 1T B  
**Page** : 1 of 5

### 1. IDENTIFICATION OF PREPARATION AND OF COMPANY

**Full name** Oasis High Build Traffic Paint(C.R)

**Manufacturer** Al Gurg Leigh's Paints LLC,  
P.O.Box 22334,  
Sharjah,  
UAE

Telephone: +971 (0) 65 343 919

Fax: +971 (0) 65 343 983

**Description** A quick drying traffic paint based on a special blend of alkyd and chlorinated rubber resins. Suitable for application of traffic lines as well as maintenance of existing thermoplastic applied road marking.

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

The following ingredients have recognised health effects or exposure limits, and are present in concentrations above the limits laid down in the Chemicals (Hazard Information and Packaging for Supply) Regulations 1994 (CHIP 2).

Substance	Weight in Paint	Classification	Risk Phrases*	CAS Number
Xylene	20-40%	Xn	R20/21 R10	1330-20-7

\*For full details of R-phrases, see Section 16.

### 3. HAZARDS IDENTIFICATION

Xn	R20/21	Harmful by inhalation and contact with skin
	R10	Flammable

### 4. FIRST-AID MEASURES

**In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.**

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.

**Eye contact** Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

**Skin contact** Remove contaminated clothing. Wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do NOT use solvents or thinners.

**Ingestion** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

## **5. FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

Use alcohol resistant foam, carbon dioxide, dry powder or water spray/mist. Do NOT use water jet.

### **Recommendations**

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire-fighting to enter drains or water courses.

---

## **6. ACCIDENTAL RELEASE MEASURES**

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Do not allow to enter drains or water courses. Clean preferably with a detergent; avoid the use of solvents. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the National Rivers Authority.

---

## **7. HANDLING AND STORAGE**

### **Handling**

Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid concentrations higher than the occupational exposure limits.

The Manual Handling Regulations may apply to the handling of containers/packages of this product. The following guide weight indicators are given to enable users to carry out assessments.

<b>Package</b>	<b>Weight</b>
3.8 litre unit	5.02kg
5USG	24.97kg

Additionally the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non-sparking tools should be used.

Ventilation and extraction must be arranged so that all parts of the workplace are properly ventilated i.e. there are no recesses or pockets where high vapour concentrations are allowed to build up.

If there is any doubt about the adequacy of the ventilation/extraction of solvent vapour, regular monitoring of confined workplaces should be carried out.

Avoid skin and eye contact. Avoid inhalation of vapour. Smoking, eating and drinking should be prohibited in areas of storage and use.

For personal protection, see Section 8.

Never use pressure to empty; the container is not a pressure vessel.

Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.

### **Storage**

Although the storage of this product is not subject to specific statutory requirements, the principles contained in the HSE guidance note Storage of Flammable Liquids in Containers, should be observed.

Observe the label precautions. Store between 5°C and 35°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are open should be properly re-sealed and kept upright to prevent leakage.

The principles contained in the HSE guidance note Storage of Packaged Dangerous Substances should be observed when storing this product. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

---

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Engineering Measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see 'Personal Protection' below).

### **Exposure Limits**

Occupational Exposure Standards and/or Maximum Exposure Limits have been established by the Health and Safety Commission or recommended by the supplier for certain of the ingredients. OELs are taken from the current version of EH40 except those marked 'Sup', which are assigned by the supplier of the substance.

<b>Substance</b>	<b>Occupational Exposure Limits</b>		<b>Notes</b>
	<b>8 hr TWA<sup>1</sup></b>	<b>15 min STEL<sup>2</sup></b>	
Xylene	100.00ppm(OES)	150.00ppm(OES)	
	<sup>1</sup>	Long term exposure limit - 8 hour time weighted average	
	<sup>2</sup>	Short term exposure limit - 15 minute reference period	
	OES	Occupational exposure standard	

Further guidance on OES/MEL and the assessment of occupational exposure to harmful materials, including mixed exposures, is given in HSE Guidance Note EH40.

### **Personal Protection**

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet requirements of the COSHH Regulations.

**Respiratory Protection** If exposure to hazardous substances identified above cannot be controlled by the provision of local exhaust ventilation and good general extraction, suitable respiratory protective equipment should be worn.

**Hand Protection** When skin exposure may occur, advice should be sought from glove suppliers on appropriate types.

Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

**Eye Protection** Eye protection designed to protect against liquid splashes should be worn.

**Skin Protection** Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleanser.

### **9. PHYSICAL PROPERTIES**

Physical State	Viscous liquid
Odour	Characteristic odour
Colour	Yellow, White, Black & Red
Density	1.27-1.42 g/cm <sup>3</sup>
Viscosity	5-7 poise at 20°C in cone and plate
Flash Point	28°C
Volatile Organic Content	460g/ltr
Explosion Limit - lower	0.6%
Water Solubility	Nil

---

### **10. STABILITY AND REACTIVITY**

Stable under the recommended storage and handling conditions (see Section 7).

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

---

### **11. TOXICOLOGICAL INFORMATION**

There is no data available on the product itself.

Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eye may cause irritation and reversible local damage.

Ingestion may result in the following effects: sore throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea. Other effects may be as described for exposure to vapours.

---

### **12. ECOLOGICAL INFORMATION**

There is no data available on the product itself.

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

---

### **13. DISPOSAL CONSIDERATIONS**

Do not allow to enter drains or water courses, or dispose of where ground or surface waters may be affected.

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet, advice should be obtained from the Environment Agency whether the special waste regulations apply.

---

#### **14. TRANSPORT INFORMATION**

##### **Transport within the user's premises**

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

##### **Transport Classification**


UN Number	1263	Shipping Name	Enamel
Class	3	Packing Group	III
Trem Card	30G35	Category	3
MFAG	310	Marine Pollutant	Yes

This information does not apply to carriage by air. Please contact the Export Department of Al Gurg Leigh's Paint if transport by air is required.

---

#### **15. REGULATORY INFORMATION**

The product has been classified and labelled for supply in accordance with the CHIP 2 regulations as follows:-



The information contained in this data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation.

The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

---

#### **16. OTHER INFORMATION**

Full details of R-phrases are as follows:-

R10	Flammable
R20/21	Harmful by inhalation and in contact with skin
R36/38	Irritating to eyes and skin
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
N	Dangerous for the environment
Xn	Harmful
Xi	Irritant

Text for S phrases

S2	Keep out of reach of children
S16	Keep away from sources of ignition – No smoking
S24/25	Avoid contact with skin and eyes
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28	After contact with skin, wash immediately with plenty of soap and water or a

**Product Reference** : Oasis High Build Traffic Paint (C.R.)  
**Date of Issue** : 20/06/2010

**Issue** : 1T B  
**Page** : 6 of 6

---

S29	recognized skin cleaner.
S38	Do not empty into drains
S51	In case of insufficient ventilation, wear suitable respirator equipment
	Use only in well ventilated areas

The information in this data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations 1994.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use are outside the supplier's control, the user is responsible for ensuring the requirements of relevant legislation are complied with.

The information contained in this data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in:

- The Chemical (Hazard Information and Packaging for Supply) Regulations 1994
- Control of Substances Hazardous to Health 1994
- Manual Handling Operations Regulations 1992
- Environmental Protection (Duty of Care) Regulations 1992
- Occupational Exposure Limits, EH40
- The Storage of Flammable Liquids in Containers, HS(G)51
- Storage of Packaged Dangerous Substances , HS(G)71
- The Approved Guide to the Classification and Labelling of Substances and Preparations Dangerous for Supply (Second Edition), L63
- The Approved Supply List, L76
- The Approved Code of Practice: Safety Data Sheets for Substances and Preparations Dangerous for Supply, L62