

## Oasis Kitchen & Bathroom (W.B) Enamel

Description:	Oasis Kitchen & Bathroom (W.B) Enamel is water based having an attractive mid-sheen finish that is tough and durable. It is suitable for the decorative and protection of interior plaster, masonry and wood surfaces, including those susceptible to condensation. It's specially designed to provide a high quality, smooth appearance that does not yellow on ageing and which is tougher than normal emulsion paints. It is quick drying with low odour.
Recommended Usage:	Recommended for use in Kitchen & bathrooms. It has been specifically designed for areas that are required to withstand repeated washing and scrubbing. Not recommended for external use.
Pack Size:	1 litre, 1 USG [3.78L] , 5 USG [18.9L]
Physical properties:	
Finish:	Smooth and Sheen Finish
Colour range:	Available in Select Colours only. Contact AGP Office / Nearest dealer outlet.
Volume (Solids. %):	38 ± 2%
Specific gravity:	1.27 ± 0.03
Theoretical spread rate:	12.6 m <sup>2</sup> /litre at 30 microns DFT
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	30 minutes
Recoat Window:	1 -2 hours
	The given data must be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site
Surface Preparation:	<ul style="list-style-type: none"> <li>• Surfaces must be clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose flaking material must be removed by scraping or brushing with a stiff bristle brush.</li> <li>• Use suitable filler for smaller cracks and holes.</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• Stir thoroughly before use</li> <li>• Use brush, roller or spray.</li> </ul> <p>Ready to use*[*Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts paint]</p> <ul style="list-style-type: none"> <li>• Avoid painting in direct sunlight</li> <li>• Store the paint in a cool place.</li> </ul>
Recommended System:	<ul style="list-style-type: none"> <li>• On previously painted surfaces in good condition and where similar colours are used, 1 coat may be sufficient.</li> <li>• On new and bare surfaces prime with 1 coat of Oasis PVA Primer or Oasis Acrylic Primer.</li> <li>• Apply 1-2 coats of Oasis Stucco, if needed.</li> <li>• Apply 2 full coats of Oasis Kitchen &amp; Bathroom (W.B) enamels.</li> </ul> <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>



## Oasis Kitchen & Bathroom (W.B) Enamel

Health, Safety and

Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately
- Avoid contact with skin and eyes
- Do not empty into drains
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Oasis Enamels

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

