



# TECHNICAL DATA

## PRODUCT: OASIS Q.D SPECIAL ENAMEL

<b>Description</b>	:	Oasis Q.D Special enamel is specially developed product for structural steel works, tanks, and gas bottles etc... The unique properties of the alkyd makes the paint to dry very fast. Ideally suited for application to steel structures primed with Oasis Q.D Undercoat. However, the product can be applied without the use of any primer also.
<b>Volume Solids (%)</b>	:	52±3%
<b>Flash Point</b>	:	Above 25°C
<b>Specific Gravity (Kg/Ltr)</b>	:	1.1 (May vary with shade)
<b>Colours</b>	:	Limited range
<b>Pack Size</b>	:	1 USG and 5 USG.
<b>Theoretical Spread Rate (m<sup>2</sup>/Ltr)</b>	:	14.2
<b>@ Dry Film Thickness</b>	:	35 µm
<b>@ Wet Film Thickness</b>	:	67 µm
		<i>Spreading rates are calculated and due allowance for loss and wastage should be made.</i>
<b>Drying Time to Touch</b>	:	5 mins @ 35 µm dft @ 35°C 10mins @ 35 µm dft @ 25°C These figures are given as a guide only. Factors such as air movement and humidity must also be considered.
<b>Drying Time to Overcoat</b>	:	Not normally required.
<b>Cleanser or Thinner</b>	:	Thinner # 2 or 29
<b>Application Notes</b>	:	Dilution up to 100 % by volume may be required according to type of equipment and application method.
<b>Application Methods</b>	:	Conventional, airless spray, or dipping .
<b>Surface Preparation</b>	:	Ensure surface is dry and free of oil, grease, rust, dust, loose particles, powder paint, etc.

## SYSTEM INFORMATION

One coat Oasis Q.D Primer  
One coat Oasis Q.D Special Enamel

## SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (READ THIS SECTION BEFORE USE)

### SOLVENT BASED PAINT PRODUCT

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE. Refer to your COSSH Assessment.
- When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Remove splashes from skin : use soap and water or a recognised skin cleaner.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into wadis, drains or watercourses.
- Contains no added mercury.

\*This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department.

March 2004

Issue 1: Revision :1

For further information please contact:-



### AL GURG LEIGH'S PAINTS L.L.C.

P.O.Box: 22334, Sharjah, U.A.E. Tel.: (+971)6-5343919, Fax: (+971)6-5343983,

P.O.Box: 70024, Abu Dhabi, U.A.E. Tel.: (+971)2-6416353, Fax: (+971)2-6416352

E-mail: [enquiries@algurgleighpaint.ae](mailto:enquiries@algurgleighpaint.ae)