

Oasis Solvacryl

Description:	Oasis Solvacryl is a solvent based pure acrylic topcoat, with long lasting, non-yellowing performance. It has excellent gloss retention and adhesion, properties while providing good resistance to water and climatic conditions. Additionally, it can be used for over coating on any Oasis Trushield textures to gain better durability.
Recommended Usage:	<ul style="list-style-type: none"> • Topcoat for interior, exterior masonry and plaster surfaces. • Topcoat for Oasis Trushield texture coatings. • Topcoat on steel and wooden surfaces.
Pack Size:	1 USG [3.78L], 5 USG [18.9L].
Physical properties:	
Finish:	Smooth and Glossy
Colour range:	Refer Oasis shade card.
Volume (Solids. %):	38 ± 2%
Specific gravity:	1.1 ± 0.05
Theoretical spread rate:	12.6m ² /litre at 30 microns DFT
Flash point:	40°C
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface Dry:	30 minutes
Recoat Window:	3 -4 hours
	The given data is meant to be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Recommended System:	<ul style="list-style-type: none"> • On previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient. • On new and bare surfaces; prime with Oasis Acrylic Primer. • Apply 2 coats of Oasis Trushield Texcoat. • Apply 2 coats of Oasis Solvacryl. <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>
Surface Preparation:	<ul style="list-style-type: none"> • Surfaces must be clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose flaking material must be removed by scraping or brushing with a stiff bristle brush. • Use suitable filler for smaller cracks and holes.
Application:	<ul style="list-style-type: none"> • Stir thoroughly before use. • Use brush, roller or spray. • Ready to use. [Depending on site conditions the paint can be diluted with maximum 1 part Oasis Thinner No: 3 to 10 parts paint.] • Avoid painting in direct sunlight. • Store the paint in a cool place.



Oasis Solvacryl

Advantages:

One component Acrylic paint, easy to apply, excellent resistance to water, weather and U.V. resistance. Dry film has excellent non-yellowing properties.

Health, Safety
and Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately
- Avoid contact with skin and eyes
- Do not empty into drains
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

