

TECHNICAL DATA

PRODUCT: OASISFLOOR 8716

Description : Oasisfloor 8716 is multi component solvent free epoxy coating system

Features :

- Self-smoothing and broadcast systems for concrete and cement screeds with durable medium to heavy wear e.g. storage and assembly halls, maintenance workshops, garages, loading ramps
- The broadcast system is recommended for multi-storey and underground car parks, maintenance hangars and for wet process areas such as beverage and food industry etc.
- Easy to apply by notch trowel designed for application at total thickness up to 2mm.
- Wide range of uses in different type of exposure condition
- Smooth, cleanable floor, Excellent adhesion, Provides long-lasting protection to concrete
- Can be top coated with epoxy or PU top coats

Recommended use :

- Garages, car parks, car workshops Service stations, Loading ramps, Pedestrian walkways
- Aircraft hangers and maintenance areas
- Industrial and commercial warehouses
- Laboratory floors
- Pharmaceutical plants
- Automotive service station
- Power plants
- Waste water and sewage treatment plants

Floor Coating System :

- Self-smoothing system 0.5 - 2.0 mm –**
Primer: 1 x Oasisfloor sealer 8766
Wearing course: 1 x Oasisfloor 8716
- Broadcast system approx. 4 mm:**
Primer: 1 x Oasisfloor sealer 8766
Base Coat 1 x Oasisfloor 8716
Broadcasting: quartz sand (0.4 - 0.7 mm) broadcast to excess
Seal coat: 1 x Oasisfloor 8716

System Information :

Selflevelling Smooth System	OASISFLOOR SEALER 8766	0.3-0.55KG/SQM
	OASISFLOOR 8716	1.9KG/SQM/1MM
Selflevelling Antiskid System	OASISFLOOR SEALER 8766	0.3-0.55KG/SQM
	Base Coat:- OASISFLOOR 8716 (300-500MICRONS)	0.6-0.95KG/SQM
	Broadcasting aggregates - Medium Duty	0.6KG/SQM
	Broadcasting aggregates - Heavy Duty	2.0 KG/ SQM
	OASISFLOOR 8716 (300-500MICRONS)	0.6-0.95KG/SQM

March 2013
Issue 1: Revision:0



For further information please contact –
AL GURG PAINTS L.L.C
 Head Office & Factory – P.O. Box 22334,
 Sharjah, U.A.E
 Tel : (+971)6-5343919 Fax : (+971)6 343983
 E-mail : enquiries@agp.ae
 Web : www.aglpuae.com

TECHNICAL DATA

PRODUCT: OASISFLOOR 8716

Colours	:	in desired shades
Volume Solids (%)	:	99%±1
Flash Point	:	NA
Specific Gravity (Kg/Ltr)	:	1.8±2% (May vary with shade)
Mixing ratio	:	Base – 85 parts by Weight Additive – 15 parts by Weight
Pack Size	:	Base - 17 kg Additive - 3 kg
Cleanser or Thinner	:	OT 5
Application Notes	:	Suitable for application over suitable concrete sealer or intermediate coat.
Application Methods	:	Notch trowel/Roller/Brush
Surface Preparation	:	Ensure surface to be coated are dry and free from all traces of surface contaminants.

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (READ THIS SECTION BEFORE USE)

SOLVENT BASED PAINT PRODUCT

- Ensure good ventilation during application and drying. Do not breathe vapour/spray.
- When applying by spray inside, wearing of air supplied breathing equipment will always be necessary. All respiratory equipment must be suitable for the purpose and meet an appropriate standard.
- When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove splashes from skin: use soap and water or a recognized skin cleaner.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook.
- Do not empty into wadis, drains or watercourses.
- Contains no added lead, Mercury and Chromium containing compounds

This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department.
